



MAX PREP

# FEATHER-IT

## Finish Coat and Smoothing Compound



**Rapid drying** | Install floor coverings after 30 minutes

**Easy to install** | Feather to 3mm in one application

**Coverage** | 4.5kg bag covers up to 30m<sup>2</sup> as a skim coat

### DESCRIPTION

MJS FEATHER-IT provides a smooth finish coat for various substrates that will receive a floor covering. MJS FEATHER-IT allows for installation of most floor coverings in as little as 30 minutes on suitable substrates like concrete, wood, ceramic and quarry tile without a primer. It is suitable for residential and light commercial areas.

### SURFACE PREPARATION

Concrete floors must be structurally sound, clean and free of dirt, dust, oil, curing and sealing compounds and any other surface contaminant which may act as a bond breaker. Where required, mechanically clean the floor using recommended preparation methods such as shotblasting, scarifying, diamond grinding, shaving or other acceptable methods to a suitable surface. Acid etching is not an acceptable method of cleaning the subfloor. Do not use solvents or sweeping compounds. Subfloor temperatures must be a minimum of 10°C.

### MIXING RATIO

Depending on site conditions, applicators preference and the finished surface requirements, 2–2.25L of water to 4.5kg of powder.

### MIXING

MJS Max Prep repair products react and harden quickly when mixed with water. Thorough mixing in the shortest possible time is essential to ensure a lump free, slump resistant mortar. Always mix the powder into the water. Mechanical mixing using a mixing paddle and electric drill will produce a creamier, smoother consistency. Do not overwater.

### APPLICATION

MJS FEATHER-IT is easily applied to any prepared surface using a steel trowel. Apply sufficient pressure to fill all defects and to fine the product into the subfloor surface. It is not necessary to leave a minimum thickness on the substrate. Use the least amount possible to obtain the desired smoothness.

### THICKNESS

MJS FEATHER-IT can be applied from a true fine edge up to 3mm in one application.

### POT LIFE

Approximately 18 minutes at 23°C.

### INSTALLATION OF FLOORING

As soon as the MJS FEATHER-IT can be walked on without damaging the surface (approx 30 minutes), floorcoverings such as vinyl, carpet and ceramic tile can be installed. When installing a skim coat of MJS FEATHER-IT over non-porous surfaces such as ceramic tiles or vinyl, always refer to the adhesive supplier for their recommended installation procedure.

### COVERAGE

As a concrete skim coat up to 30m<sup>2</sup> can be achieved and even more over plywood. At 1mm 20m<sup>2</sup> can be achieved over concrete.

### STORAGE

MJS FEATHER-IT has a shelf life of 12 months when stored in the original unopened packaging in a dry place at 23°C and 50% relative humidity.

### SAFETY DATA

Causes skin irritation and serious eye damage. May cause respiratory irritation. Suspected of causing genetic defects.



MAX PREP

# FEATHER-IT

## Finish Coat and Smoothing Compound



In case of contact with the eyes rinse with running water until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust/fumes/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents, dispose of packaging thoughtfully and recycle where possible. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS). Contact MJS for the Safety Data Sheet (SDS). At times, updates can occur to data. To ensure you have the most current technical and safety information, please consult the latest data sheets found on the product page at [www.mjsfloorcoverings.com.au](http://www.mjsfloorcoverings.com.au).



**MAX PREP**

## CONTACT

### QLD

**Mansfield** (07) 3347 7300

**Townsville** (07) 4727 6500

**Bowen Hills** (07) 3514 5700

**Burleigh** (07) 5586 9800

**Cairns** (07) 4245 8300

**Mackay** (07) 4864 3500

**Maroochydore** (07) 5475 8100

**Toowoomba** (07) 4592 4700

### NSW

**Wetherill Park** (02) 9616 1500

**Newcastle** (02) 4965 2600

**Seven Hills** (02) 8672 2100

**Tamworth** (02) 0407 454 500

**Wollongong** (02) 42539000

### ACT

**Fyshwick** (02) 6212 9400

### VIC

**Sunshine** (03) 9351 7400

### SA

**Adelaide** (08) 8178 5300

### TAS

**Hobart** (03) 6242 8800

### NT

**Darwin** (08) 7922 9700

## DISCLAIMER

The technical details, recommendations and other information contained in this data are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard. Our instructions and recommendations are only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.