



# MAX BOND

## PRODUCT DATA SHEET

### M88 FLOOR & WALL VINYL ADHESIVE

#### PRODUCT DESCRIPTION

Max Bond Enviro 88 is high performance Floor & Wall Vinyl Adhesive with Low VOC that conforms to the Green Star Building Standard. It is an acrylic based adhesive designed for the installation of commercial and domestic sheet vinyl. It is not recommended for the installation of linoleum or LVT.

It has an excellent plasticizer resistance and is formulated to provide good open times and exhibit excellent "re-bond" characteristics. Internal use only.

This adhesive is suitable for use over absorbent heated subfloors. Please refer to AS1884-2012 including clause 4.1.3 that explains time heating needs to be turned off for.

#### SURFACE PREPARATION

To be in accordance with The current Australian/NZ Standard 1884 "Floor Coverings – Resilient Sheet and Tiles – Laying and Maintenance Practices". All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications should be greater than 10 degrees C. Substrate must be absorbent to enable the adhesive to dry & cure.

Highly absorbent wooden or concrete subfloor surfaces are to be primed with MAX BOND Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings.

#### APPLICATION

Spread adhesive with a 1.6mm x 1.6mm x 1.6mm 'V' Notched trowel. Some domestic sheet vinyl may require a fine 1.6mm x 0.8 x .08 trowel to prevent adhesive 'show through'. Adhesive can be between 10-20 minutes. It is good practice to place a small piece of floorcoverings into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes before re-checking every few minutes thereafter. Always ensure wet transfer has accrued to floorcovering.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roll weight, prior to the adhesive setting. Do not allow heavy traffic for 24 hours.

All seams for domestic vinyl should be seam-sealed using suitable vinyl seam sealer.

#### CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

#### TYPICAL PROPERTIES

Appearance:	Cream / White Base Acrylic
Solids:	Approx. 70%
Viscosity:	Creamy Paste
Shelf Life	Up to 1 year in sealed container at 20°C
Freezability:	Do not freeze Container
Size:	15 Litre plastic pail
Tack-up:	10-15 minutes at 20°C

*Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS website.*

*Updated 11/03/21*



**QUEENSLAND**  
Brisbane  
MJS Floorcoverings  
35 Dividend St  
Mansfield 4122  
Ph: 07 3347 7300  
Fax: 07 3343 9792

**NSW**  
Sydney  
MJS Floorcoverings  
2/4-7 Potter Close  
Wetherill Park 2164  
Ph: 02 9616 1500  
Fax: 02 9616 1502

**VICTORIA**  
Melbourne  
MJS Floorcoverings  
82 Endeavour St  
Sunshine 3020  
Ph: 03 9351 7400  
Fax: 03 9351 7402

**TASMANIA**  
Hobart  
MJS Floorcoverings  
101 Albert Rd  
Moonah 7000  
Ph: 03 6242 8800  
Fax: 03 6242 8802

**NORTHERN TERRITORY**  
Darwin  
MJS Floorcoverings  
Unit 4/124 Coonawarra Rd  
Winnellie NT 0821  
Ph: 08 7922 9700  
Fax: 08 7922 9702

**SOUTH AUSTRALIA**  
Adelaide  
MJS Floorcoverings  
22 Ridley Street  
Hindmarsh SA 5007  
Ph: 08 8178 5300  
Fax: 08 8178 5302

**WESTERN AUSTRALIA**  
Perth  
MJS Floorcoverings  
Opening soon