

INTERFACEFLOR WATER BASED SEAM ADHESIVE

InterfaceFLOR Water Based Seam Adhesive is an adhesive used for bonding the seams together in InterfaceFLOR GlasBac carpet tile installation.

Application

Seams must be clean, dry and free from adhesive. Starting at one end of the seam, apply a 3.0mm bead along the length of the seam using a Seam Adhesive Applicator.

Butt both edges of the seam together whilst seam sealer is still wet.

Remove excess wet seam sealer with clean damp cloth.

Allow to fully dry before subjecting the seam to any traffic.

Clean Up

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using Roberts 550 Latex/Acrylic Adhesive Remover applied to a damp cloth then rubbed gently over the dried adhesive. Roberts 550 is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

Note:

The finished seam should not be subjected to excessive traffic eg. castor chairs or excessive cleaning practices.

If spillage on the seam occurs, prevent any traffic on the seam until the spillage has been cleaned and fully dried. Do not allow spillage to remain on the seam for more than 48 hours.

Coverage

Approx 50Lm per 1litre depending on applicator and site conditions.

Safety and Handling

Material Safety Data Sheet available upon request.

Typical Properties

Appearance Base Viscosity Shelf Life

Package

Freezability

White cream Acrylic copolymer Cream 12 months in a sealed container @ 20C 1 litre units Do not freeze

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia P.O. Box 147, Kilsyth, Victoria 3137 Australia Telephone: (03) 9728 1644 • Facsimile: (03) 9728 6009 E-mail: info@rlapolymers.com.au • Web: www.rlapolymers.com.au





67 Dalgety Drive (P.O. Box 97-575) Manukau City, Auckland, New Zealand Telephone: (9) 268 0301 Facsimile: (9) 268 0305

RLA 044B

P R O D U C T D A T A

