



MAX BOND

PRODUCT DATA SHEET

M360 1-PART MS VINYL ADHESIVE

PRODUCT DESCRIPTION

Max Bond MS360 is a 1-part MS adhesive designed for the installation of PVC commercial and domestic sheet vinyl, LVT & LVP. It is also suitable for the installation of sanded back rubber flooring, Linoleum and Artificial Grass. It has good plasticiser resistance and protection from biodegradation, making it suitable for indoor and outdoor use in wet and dry areas.

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond including dust, paints, and old floorcoverings. All surfaces must be prepared in accordance with current Australian Standards 1884 Floor Coverings Resilient Sheet including moisture testing.

IMPORTANT: The minimum sub floor temperature prior to commencing preparation of adhesive application is 15°C, in cold weather, the adhesive should be warmed up in a heated environment before use.

The maximum room humidity prior to commencing adhesive application is 75%, DO NOT apply adhesive on subfloors with rising damp.

DIRECTIONS FOR USE

Apply adhesive using a suitable trowel as listed below for your application spread evenly to prepared substrate held at approximately 60-degree angle. Best results are when the adhesive is allowed to have between 5 – 20 minutes open time prior to installing floorcovering in to wet film of adhesive depend on atmospheric conditions. Always ensure complete transfer of adhesive to the floorcovering has occurred. Complete installation according to manufacturer's instructions and current AS1884 standards. Roll installation prior to adhesive setting with the recommended weight roller. Do not allow traffic or water for 24 hours after installation.

INSTALLATION IN COOL ROOMS AND OVER HEATING SYSTEMS

Max Bond MS360 is suitable for use in cool rooms and freezers as well as over underfloor heating systems, it is also suitable for insulation of floor coverings in areas with higher temperatures of up to 50°C for prolonged period. Please confirm with the flooring manufacturer on whether their product is suitable for use in these conditions. For these types of installations, subfloor temperature must be maintained at minimum 15°C and air temperature at 18°C

for at least 3 days prior and at least 3 days after the installation.

COVERAGE

Flooring type	Trowel Size	Coverage
LVT vinyl and PVC with smooth back surface	V1	Approx. 16 - 20 m ² per pail
Linoleum, rubber and PVC flooring with textured back surface	V2	Approx. 10 - 12 m ² per pail
Synthetic grass, needle fleece flooring	V3 or larger notch required on very textured products	Approx. 6 - 8 m ² per pail

CLEAN UP

Clean tools immediately after use with MJS adhesive remover. Dried adhesive may be softened using a suitable solvent like Max Bond SC Solvent Cleaner. Note: Do not use SC on finished floorcoverings.

TECHNICAL DATA

Base: MS Polymer
 Open time: 5 – 20 minutes
 Working Time: Up to 35 minutes depending on site conditions
 Curing Time: 24 – 48 hours
 Shelf Life: 12 months in sealed container at 20°C
 Packaging: 7.5kg plastic foil sealed pails

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling, and transport is available in the Safety Data Sheet (SDS), available on MJS website.

Updated 07/06/2023.



QUEENSLAND

Brisbane
 MJS Floorcoverings
 35 Dividend St
 Mansfield 4122
 Ph: 07 3347 7300
 Fax: 07 3343 9792

NSW

Sydney
 MJS Floorcoverings
 2/4-7 Potter Close
 Wetherill Park 2164
 Ph: 02 9616 1500
 Fax: 02 9616 1502

VICTORIA

Melbourne
 MJS Floorcoverings
 82 Endeavour St
 Sunshine 3020
 Ph: 03 9351 7400
 Fax: 03 9351 7402

TASMANIA

Hobart
 MJS Floorcoverings
 101 Albert Rd
 Moonah 7000
 Ph: 03 6242 8800
 Fax: 03 6242 8802

NORTHERN TERRITORY

Darwin
 MJS Floorcoverings
 Unit 4/124 Coonawarra Rd
 Winnellie NT 0821
 Ph: 08 7922 9700
 Fax: 08 7922 9702

SOUTH AUSTRALIA

Adelaide
 MJS Floorcoverings
 22 Ridley Street
 Hindmarsh SA 5007
 Ph: 08 8178 5300
 Fax: 08 8178 5302

WESTERN AUSTRALIA

Perth
 MJS Floorcoverings
 Opening soon