

Product Name: Max Seam Silicone Release Dispenser Pack Heat Bond Tape #MSDP Issue date November 2015
Not classified as Hazardous according to the criteria of Worksafe Australia

Company Name BBS Flooring Products Pty Ltd (ABN 79 100 338 896)
 Address 2 / 75 Zenith Rd Dandenong Vic 3175, Australia
 Tel +61 (03) 97932-2244 Fax +61 (03) 9793-4488 Email info@bbsfp.com

IDENTIFICATION

Product name Max Seam Silicone Release Dispenser Pack Heat Bond Tape #MSDP
 Other names Not Available
 U.N. Number None Allocated
 Correct Shipping Name Not Applicable
 Dangerous Goods Class Not Applicable
 Hazchem Code Not Applicable
 E.P.G Not Applicable
 Packaging Group Not Applicable
 Poison Schedule Not Scheduled
 Product Use Heat activated carpet seaming tape

PHYSICAL DATA

Appearance Light amber hotmelt adhesive on a brown Kraft paper
 Melting point 80 - 120°C
 % volatiles (w/w) Nil
 Specific gravity 0.98
 Flash point Not Applicable
 Flammable Limit LEL and UEL Not Applicable

INGREDIENTS

<u>Chemical Entity</u>	<u>CAS</u>	<u>Proportion</u>
EVA Copolymer	24927/78/8	10 / 30%
Synthetic Resin	proprietary	30 / 60%
Hydrocarbon Wax	63231/60/7	10 / 30 %

HEALTH EFFECTS

Acute - Ingestion None known but swallowing may result in choking.
Acute - Eye Fumes from heated product can be mildly irritating to the eyes
Acute - Skin Molten material may cause burns
Acute - Inhalation Vapour and fumes are mildly irritating to mucous membranes and respiratory tract and may result in nausea
Chronic Available data indicates low toxicity. Long term exposure to this product type indicates no danger to health when handled in accordance with good industrial practices

FIRST AID

Ingestion If solid is swallowed, rinse mouth immediately with water and give water to drink. For molten material seek immediate medical assistance.
Eye Irrigate immediately with copious quantities of water for at least 15 minutes holding eyelids open. Seek immediate medical assistance. In case of burns treat as for "skin" and urgently seek medical assistance
Skin For burns, immediately flood burnt area with plenty of water and cover with a clean dry dressing. If molten material should contact the skin and adhere, cool quickly with running water - do not attempt to remove the adhesive from the skin. Seek medical assistance in case of burns.
Inhalation Remove victim from exposure and allow to recover. Apply artificial respiration or oxygen if required. If discomfort continues seek medical assistance.
First Aid Facilities Safety shower and eye wash station
Advise to doctor Treat symptomatically

CONTINUED OVER THE PAGE

Exposure Limits None assigned by Worksafe Australia.

Exposure standard (TWA) refers to the time weighted average airborne concentration over an eight-hour day, for a five day working week, over an entire working life. According to current knowledge, this concentration level should neither impair the health of, nor cause undue discomfort to, nearly all workers. Short term exposure limit (STEL) refers to the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour day. These exposure standards are guides to be used in the control of occupational health hazards. All atmospheric contaminants should be kept to as low as is workable and should not be used as a fine dividing line between safe and dangerous concentrations of chemicals.

ENGINEERING CONTROLS General ventilation is usually adequate. If product is to be used in a confined space local extraction is recommended.

PERSONAL PROTECTION

Respirator type Organic Vapour respirator is recommended if at risk of exposure to vapours
Eye protection Safety glasses with side shield, chemical goggles or face mask
Glove type PVC coated
Clothing Standard work overalls covering arms and legs
Foot wear Chemical resistant safety shoes or boots
Hygiene Always wash hands before smoking, eating, drinking or using toilet.

STORAGE and TRANSPORT

Storage Precautions Store in a well ventilated area away from direct sunlight and frost. Store away from foodstuffs and oxidising agents. Keep containers closed when not in use.
Transport Not classified as a dangerous good for the purposes of transportation.

SPILLS and DISPOSAL

Spills and leaks Contain molten material using absorbent material such as sand. When adhesive has set, collect, seal in containers and identify for disposal. Area may be hosed down to remove any remaining material but, where possible water should be collected for disposal.
Disposal Refer to state land waste management authority. Normally suitable for disposal at approved land waste site or for incineration by approved agent

FIRE AND EXPLOSION HAZARD

Fire / Explos. Hazard Not flammable under normal conditions. Combustible - on burning will emit toxic fumes.
Fire Fighting Fire fighters to wear self-contained breathing apparatus if risk of exposure to vapour or products of combustion
Extinguishing Media Foam, carbon dioxide or dry chemical powder .use water spray to cool down fire exposed surfaces, but do not use on molten hot melt.
Hazardous reaction Hazardous reactions will not occur.

Contact BBS on +61 (03) 9793-2244 during office hours
Out of hours contact Poison Information Centre: 131126

Although the information and recommendations set down here in this document are presented in good faith and believed to be accurate, BBS makes no representations as to the completeness and accuracy of said document. In no event will BBS be responsible for damages of any nature whatsoever resulting from the use of or reliance upon this information. No representations or warranties, either expressed or implied, or merchantability, fitness for purpose or any other nature are made hereunder with respect to the product to which this information refers.