

Product Data Sheet



Max Bond

Powerhold Pressure Sensitive Adhesive

PRODUCT DESCRIPTION

Powerhold Pressure Sensitive Adhesive is water based type adhesive designed for installing Carpet Tiles and VCT (Vinyl Composition Tiles)

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants. All surfaces must be prepared in accordance with current relevant Australian Standards 1884-2012 Floor Coverings Resilient Sheet or 2455.2.2007 including moisture testing. It is recommended that all highly absorbent sub floors be primed with MJS Max Prime Acrylic Floor & Wall Primer prior to the application of adhesive.

The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.

APPLICATION

Apply adhesive using a long nap roller for smooth backed carpet tiles and a 1.6mm x 1.6mm x 1.6mm "V" notched trowel for VCT & felt or textured backed carpet tiles. The adhesive should be allowed to clear prior to floor covering being placed into the tacky adhesive film. Clear is when the adhesive changes from white wet adhesive to dry clear tacky film of adhesive. The 'clear' time will depend on atmospheric conditions. Complete installation according to manufacture instruction. Roll installation on completion with the recommended weight roller. Do not allow heavy traffic for 24 hours. Don't allow any dust or other contaminants to come in contact with adhesive film prior to application of floorcoverings.

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be softened using a suitable solvent.

TYPICAL PROPERTIES

Appearance	Cream/White
Base	Acrylic
Solids	Approx. 50%
Viscosity	Creamy Paste
Shelf Life	Up to 1 year from manufacturing date in sealed container at 20°C
Freezability	Do not freeze
Container Size	1 & 4 Litre plastic pail
Trowel Size	Long nap roller 1.6mm x 1.6mm x 1.6mm 'V' notched trowel for VCT
Coverage	Up to 5 m ² per litre using "V1" trowel. Up to 7 m ² per litre using long nap roller.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.



Floorcoverings

March 2016

DISTRIBUTED BY:

QUEENSLAND Brisbane

MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 1800 063 299

NSW Sydney

MJS Floorcoverings
7 Walker Place
Wetherill Park 2164
Ph: 02 9725 5519
Fax: 02 9725 5552

VICTORIA Melbourne

MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9314 2872
Fax: 03 9314 6971

TASMANIA Hobart

MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6228 1032
Fax: 03 6228 1035

NORTHERN TERRITORY Darwin

MJS Floorcoverings
3,124 Coonawarra Rd
Winnellie 0821
Ph: 08 8947 6917
Fax: 08 8947 1528

SOUTH AUSTRALIA Adelaide

MJS Floorcoverings
22 Firth St
Bowden 5007
Ph: 08 8340 2266
Fax: 08 8340 2188

WESTERN AUSTRALIA

Perth
MANAG Distributors
28 Carbon Court
Osborne Park 6017
Ph: 08 6240 1000
Fax: 08 9445 1332