





Accredited for compliance with ISO/IEC 17025

NATA is a signatory to the ILAC Mutual Recognition was a recognition of the equivalence of testing, medical testing, calibration

OIL-WET INCLINING PLATFORM SLIP RESISTANCE TEST

Somplan 350 sheet vinyl

Prepared for: Tarkett Australia Pty Ltd

Paul Roberts

Suite 1, Level 3, 3 Columbia Court BALKHAM HILLS NSW 2153

Specimen Description: Somplan 350 sheet vinyl, 500x1000 mm.

No. of Specimens: 1 off

Surface Structure: Smooth

Specimen Preparation: Washed with water and pH neutral detergent, rinsed then dried.

Specimen Configuration: Fixed

Test Direction: Test direction not applicable.

Joint Type & Width: N/A
Air Temperature: 22°C

Test Standard: AS 4586:2013 Slip resistance classification of new pedestrian surface

materials, Appendix D - Oil Wet Inclining Platform Test

Test Shoe: Leipzig V73-SP

Test Location: ATTAR, Unit 1, 64 Bridge Road, Keysborough.

Test Date: 22 December 2020

Test Personnel: Dale Siegle and Marcus Braché

Displacement Space	Not tested	
(rounded to the nearest 0.5cm³/dm²):		
Displacement Space Assessment Group	Not tested	
(Appendix E, AS 4586 - 2013):		
Corrected mean overall acceptance angle (α _{ave})	10°	
(rounded down to the nearest degree):		
Classification:	R10	

These results apply only to the specimens tested and it is recommended that before selection of flooring or paving materials the effect of service conditions, including maintenance procedures and wear on their slip resistance be checked.

Marcus Braché

Senior Engineering Technician

Approved Signatory

Dale Siegle

Reviewed By:

Compliance and Test Technician

Approved Signatory

ATTAR - Advanced Technology Testing and Research



Figure 1: Somplan 350 sheet vinyl



CLASSIFICATION CRITERIA – AS 4586 - 2013 Oil Wet Inclining Platform Test – Appendix D

Compliance

TABLE 5: CLASSIFICATION OF PEDESTRIANSURFACE MATERIALS ACCORDINGTO THE OIL-WET INCLINING PLATFORM TEST

Classification	Angle, degrees
No Classification	<6
R9	≥6 <10
R10	≥10 <19
R11	≥19 <27
R12	≥27 <35
R13	≥35