

100 SPRAY CONTACT ADHESIVE

DESCRIPTION:

MJS Max Bond 100 is a general purpose solvent based sprayable contact adhesive used for fixing laminating or laminex to various types of wood such as chipboard and hardboard. Max Bond 100 is also suitable for polyurethane foams, supported PVC, fabric, leather, rubber sheet and extrusions to each other.

METHOD OF APPLICATION:

- To obtain the best possible results, the materials to be bonded should be dry, clean and free from dust, grit, loose materials, oil or grease.
- Using conventional spray equipment, apply an even coating of adhesive to both surfaces to be bonded.
- Allow the solvent to evaporate before bonding the materials. On absorbent materials such as leather and chipboard, bonding may be within a matter of 2-3 minutes of application. On non-absorbent materials such as formica and metal a minimum of 15 minutes should be elapsed before the surfaces are bonded together.
- Contact bond the surfaces together using firm pressure.

PROPERTIES:

Appearance: Opaque yellow liquid.

Viscosity: Thin liquid.

Coverage: 6 - 8m² per litre

CLEAN UP:

Clean tools immediately after use with Max Bond SC solvent cleaner.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (SDS), available on request.

Updated 11/03/21



Fax: 08 7922 9702