

# **MFGL FAST SET LIQUID**

# PRODUCT DESCRIPTION

MJS Max Bond FGL is ideal for bonding carpet gripper, woods, metal trims, metal nosing, aluminium & many other types of products where a quick bond is required to concrete, timber and most other common building substrates. MJS Max Bond FGL has excellent resistance to high temperatures and water.

## SURFACE PREPARATION

All surfaces must be clean & sound, free of dust and any other contaminates that may affect bond.

#### **APPLICATION**

Apply thin bead of adhesive to one surface. Press the two surfaces to be bonded firmly together. Pressure may need to be applied to keep the two surfaces in contact while adhesive cures.

# **CURING TIME:**

MJS Max Bond FGL is a moisture cure system. Allow approx. Two hour curing time. This process may be accelerated by praying a light mist of water to one of the surfaces.

Thick beads will take longer to cure and will have a weaker bond than a thinner bead. The thicker the bead of FGL the more the product will tend to foam.

Always Wear Protective Gloves when using FGL, refer to MSDS for further personal safety protection.

Large extrusions should also be secured with appropriate fixing screws.

## **CLEAN UP:**

Remove any wet adhesive with Max Bond SC before it cures. When cured remove by mechanical means.

## **TYPICAL PROPERTIES:**

Appearance: Brown Liquid
Viscosity: Thin Liquid
Specific Gravity: Approx. 1.15

Updated 11/03/21



Fax: 08 7922 9702

Fax: 08 8178 5302