

MP15 MAX PRIME

PRODUCT DESCRIPTION

MJS Max Prime is a water based acrylic primer designed to prime absorbent substrates prior to the application of water-based adhesives.

FOR PRIMING

Most highly absorbent substrates such as concrete, timber, solid plaster, plasterboard, cement sheet and cementitious screeds.

STANDARDS

Australian/NZ Standard 2455.1.1995 – "Textile Floor Coverings Installation Practice".

SURFACE PREPARATION

All surfaces to be primed should be dry, smooth, and free of any contaminates that may affect final bond.

It is highly recommended that all absorbent sub floors be primed with MAX PRIME prior to the application of adhesive.

The minimum sub floor temperature prior to commencing preparation or primer application is 10°C.

TECHNICAL DATA

Appearance: White liquid

APPLICATION

Max Prime should be applied evenly over the entire sub floor by Soft Broom or Brush.

Highly absorbent sub floors may require a second coat of Max Prime. Allow first coat to dry prior to applying further coats.

CLEAN UP

Clean tools immediately after use with warm soapy water.

SHELF LIFE

Up to 12 months in sealed container at 20°C.

SAFETY & HANDLING

A Material Safety Data Sheet is available on request.

CONTAINER SIZES

15 litre plastic pails

Updated 11/03/21



Fax: 08 7922 9702

Fax: 08 8178 5302