

OF INTERFACE AUST. PTY LIMITED - ABN 39 000 692 026

34 AIRDS ROAD, MINTO NSW 2566 - TEL: (02) 8706 4632

### TEST REPORT

Client: Interface Australia PTY LTD

34 Airds Road Minto

NSW 2566 Australia

Sample Description:

Test Report No:
Sample Received Date:
Test Date:

Report Date:

R22-037A 7/08/2021 10/02/2022 25/03/2022

160z"

100% Solution Dyed Nylon 6 543g/m<sup>2</sup> on a Glasbac Backing

Client Reference: "TRUE DIMENSIONS

Sample Manufacturing:

Interface Australia

### AS/NZS 2111.4 Textile floor coverings – Tests and measurements Method 4: Determination of surface pile mass above the substrate (g/m²)

Surface Pile Mass Specimen 1 354.76g/m<sup>2</sup>
Surface Pile Mass Specimen 2 364.51g/m<sup>2</sup>
Surface Pile Mass Specimen 3 345.47g/m<sup>2</sup>
Surface Pile Mass Specimen 4 364.77g/m<sup>2</sup>

Surface Pile Mass Mean: 357.38g/m<sup>2</sup>

Coefficient of Variation: 2.57%

Corrected Surface Pile Mass Mean: 361.68g/m<sup>2</sup>

Standard Allowance: 5.75%

Shearing apparatus: Band knife

The surface pile mass has been estimated to take into account the penetration of backing components into the base of the pile. The accuracy of estimation methods has not been established.

Test conducted in accordance with AS/NZS 2111.4

Page 1 of 5

Accreditation No.2834.

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the test, calibrations and/or measurements included in this document are traceable to Australian/ International Standards.

This report may not be reproduced except in full and shall be rendered void if amended or altered. The results on this report are related only to the items tested.

KARTHIK BHASKARAN Materials Scientist

APPROVED SIGNATORY



# SYDNEY CARPET LAB

34 AIRDS ROAD, MINTO NSW 2566 - TEL: (02) 8706 4632

### **TEST REPORT**

Client: Interface Australia PTY LTD

34 Airds Road Minto

NSW 2566 Australia

Test Report No: Sample Received Date:

R22-037A 7/08/2021

Test Date: 10/02/2022 Report Date: 25/03/2022

Sample Description: Client Reference: "TRUE DIMENSIONS

16Oz"

100% Solution Dyed Nylon 6 543g/m<sup>2</sup> on a Glasbac Backing Sample Manufacturing:

Interface Australia

Conditioning conducted in accordance with AS 2001.1 – Preconditioning not completed. **AS/NZS 2111.1** 

Textile floor coverings - Tests and measurements Method 1: Machine-made textile floor coverings - Determination of total thickness

Thickness Specimen 1:	5.2mm
Thickness Specimen 2:	5.3mm
Thickness Specimen 3:	5.4mm
Thickness Specimen 4:	5.4mm
Thickness Mean:	5.3mm

Test conducted in accordance with AS/NZS 2111.1

#### AS/NZS 2111.5 Textile floor coverings – Tests and measurements Method 5: Determination of thickness of pile above the substrate

Surface Pile Thickness Specimen 1:	2.4mm
Surface Pile Thickness Specimen 2:	2.7mm
Surface Pile Thickness Specimen 3:	2.6mm
Surface Pile Thickness Specimen 4:	2.7mm

Surface Pile Thickness Mean: 2.6mm

Page 2 of 5

Accreditation No.2834.

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the test, calibrations and/or measurements included in this document are traceable to Australian/International Standards.

This report may not be reproduced except in full and shall be rendered void if amended or altered. The results on this report are related only to the items tested.

KARTHIK BHASKARAN Materials Scientist

APPROVED SIGNATORY



OF INTERFACE AUST. PTY LIMITED - ABN 39 000 692 026

34 AIRDS ROAD, MINTO NSW 2566 - TEL: (02) 8706 4632

### **TEST REPORT**

Client: Interface Australia PTY LTD

34 Airds Road Minto

NSW 2566 Australia Test Report No: Sample Received Date:

R22-037A 7/08/2021 10/02/2022

Test Date: Report Date:

10/02/2022 25/03/2022

Sample Description: Client Reference: "TRUE DIMENSIONS

160z"

100% Solution Dyed Nylon 6 543g/m<sup>2</sup> on a Glasbac Backing

Sample Manufacturing:

Interface Australia

Shearing apparatus: Band knife

Test conducted in accordance with AS/NZS 2111.5

#### Woolmark TM247 / Woolmark TM251 / Woolmark TM284

### Hexapod Tumbler Test – Change in Surface Structure and Colour of Textile Floorcoverings

Mean numerical Grey Scale Rating for Change of Colour 1500:	4.0
Mean numerical Scale Rating for Change of Surface Structure 1500:	4.0
Thickness Loss (mm):	0.2mm

Mean numerical Grey Scale Rating for Change of Colour 8000:	3.0
Mean numerical Scale Rating for Change of Surface Structure 8000:	3.0
Thickness Loss (mm):	0.6mm

Rating using a Grey Scale 1 to 5: were 1 (very severe change), 5 (no change)

Rating using a Structure Scale 1 to 5: were 1 (very severe change), 5 (no change) CRI Reference Scale CRI 1 – CRI 7

Page 3 of 5

Accreditation No.2834.

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the test, calibrations and/or measurements included in this document are traceable to Australian/ International Standards.

This report may not be reproduced except in full and shall be rendered void if amended or altered. The results on this report are related only to the items tested.

KARTHIK BHASKARAN Materials Scientist APPROVED SIGNATORY



OF INTERFACE AUST. PTY LIMITED - ABN 39 000 692 026

34 AIRDS ROAD, MINTO NSW 2566 - TEL: (02) 8706 4632

### **TEST REPORT**

Client: Interface Australia PTY LTD

34 Airds Road Minto

NSW 2566 Australia Test Report No: Sample Received Date:

R22-037A 7/08/2021 10/02/2022

Test Date: Report Date:

10/02/2022 25/03/2022

Sample Description: Client Reference: "TRUE DIMENSIONS

160z"

100% Solution Dyed Nylon 6 543g/m<sup>2</sup> on a Glasbac Backing

Sample Manufacturing:

Interface Australia

AS/NZS 2111.9 Textile Floor Coverings – Tests and measurements Method 9: Determination of the number of tufts per unit length and per unit area

S (Parallel to Selvedge): 38 / 100mm G (Right Angle to Selvedge): 41 / 100mm

Test conducted in accordance with AS/NZS 2111.9 Conditioning was conducted in accordance with AS2001.1.

Page 4 of 5

Accreditation No.2834.

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the test, calibrations and/or measurements included in this document are traceable to Australian/ International Standards.

This report may not be reproduced except in full and shall be rendered void if amended or altered. The results on this report are related only to the items tested.

KARTHIK BHASKARAN Materials Scientist APPROVED SIGNATORY



OF INTERFACE AUST, PTY LIMITED - ABN 39 000 692 026

34 AIRDS ROAD, MINTO NSW 2566 - TEL: (02) 8706 4632

### **TEST REPORT**

Client: Interface Australia PTY LTD

34 Airds Road Minto

NSW 2566 Australia Test Report No: Sample Received Date: R22-037A 7/08/2021 10/02/2022

Test Date: Report Date:

10/02/2022 25/03/2022

Sample Description: Client Reference: "TRUE DIMENSIONS

160z"

100% Solution Dyed Nylon 6 543g/m<sup>2</sup> on a Glasbac Backing Sample Manufacturing:

Interface Australia

**END OF REPORT** 

Page 5 of 5

Accreditation No.2834.

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the test, calibrations and/or measurements included in this document are traceable to Australian/ International Standards.

This report may not be reproduced except in full and shall be rendered void if amended or altered. The results on this report are related only to the items tested.

KARTHIK BHASKARAN Materials Scientist APPROVED SIGNATORY