

TensorGrip®

FS707

WATER BASED CARPET
TILE TACKIFIER



UNDERLAY



CARPET TILES



SNOWFLAKE
SPRAY

TECHDATA



PRODUCT DESCRIPTION

TensorGrip® FS707 is a water based pressure sensitive carpet tile tackifier. TensorGrip® FS707 has a fast application time and high coverage rate, making large floor installations quick and easy. As a water based adhesive, TensorGrip® FS707 is a healthier choice for installers, clients and the environment. TensorGrip® FS707 is suited to almost all types of backing and substrates.

ADVANTAGES

- Non flammable
- Water based
- Low odour
- Fast tack off
- Non-toxic
- Allows for repositioning

SUITABLE SUBSTRATES

- Primed concrete
- Unprimed concrete
- Primed timber
- MDF
- Subfloor Sheeting
- PVC & Vinyl backed carpet tiles
- Drop in and loose lay vinyl tiles & planks

DIRECTIONS FOR USE

- Make sure that surfaces are clean, dry and free from dirt, dust, oil, loose paint, wax or grease, etc.
- For best results, the temperature of the adhesive and the surfaces being bonded should be between 16°C - 27°C.
- Use with adequate ventilation.
- Shake the aerosol well before use.
- Hold the aerosol upside down, 60-90cm from the floor at a 30-40° angle, from waist height.
- Apply adhesive quickly and evenly onto the floor at 80-90% coverage. DO NOT let the adhesive puddle.
- Clean adhesive off the nozzle with water to avoid poor spray pattern.
- Apply slight sideways/upward pressure to the nozzle to spray adhesive.
- Allow 10-15 minutes, or until adhesive turns translucent, for the adhesive to become tacky before laying tiles
- Adhere surfaces and press together with adequate pressure.
- DO NOT FREEZE

PREPARATION & APPLICATION

Suitable subfloors include self-levelling compounds, plywood (underlayment grade), OSB, hardboard and existing non-cushion backed resilient floors (must be well bonded, sound, smooth and free of all waxes, finishes, strippers and cleaners). All paint varnish, oil, wax and any other finishes which may inhibit good bond should be removed. Repair all joints and cracks with a latex based levelling compound. Subfloors should be subject to 28 days of maturing and should have a maximum of 10.8% moisture content before using this adhesive. Do not use this adhesive above these recommendations. Subfloor preparation and moisture and PH testing must comply with industry standards, and floor-covering manufacturer's guidelines. The floor, room temperature, and the flooring materials must be maintained in accordance with floor covering manufacturer's recommendations. All subfloors should be free of dust prior to application

Tensorgrip®

FS707

WATER BASED CARPET
TILE TACKIFIER

AVAILABLE IN



AEROSOL
500 ML

COVERAGE
UP TO 60M²

COLOURS



WHITE (dries clear)

CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

System Flammability	Non Flammable propellant with water based adhesive
Dry time	0-15 minutes dependant on temp & humidity
Open Time	4+ hours depending on atmospheric conditions
Product PH	6.8
Subfloor PH	Maximum 13.2
Subfloor RH	Up to 90%
Subfloor Moisture	Up to 10.8%
SHELF LIFE	12 months from date of manufacture

HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 15°C
- Always test our adhesives to determine suitability for your particular application prior to use in production

Copyright © 2023 by Quin Global AU Ltd All rights reserved. This publication or any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of the publisher.

DISCLAIMER OF WARRANTY: The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.



Manufactured in Australia By

Quin Global AU
PO Box 6196
Queanbeyan NSW 2620

1300 857 846
www.quinglobal.com.au
sales@quinglobal.com.au