

Wallgard 2.0mm

Datasheet

Classification	Norm	Tarkett Value
Product type	EN 259-1	Homogeneous vinyl wall covering
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	2.0 mm
Total weight	EN ISO 23997	3400 g/m ²
Wear layer thickness	EN ISO 24340	2.0 mm
Surface treatment		PU SHIELD
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 15102	0019-0043-DoP-2013-07
Reaction to fire	AS/NZS 3837: Average specific extinction area	Group 1 84.3m ² /kg
Technical Performance	Norm	Tarkett Value
Colour fastness to light	ISO 105-B02	≥ 7
Chemical resistance	ISO 26987	Good Resistance
Clean room	ISO 14644-1	ISO class 4
Wetroom room	GBR Class VT	Approved
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Recycled content		25,5 %
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m ³)
Formaldehyde emission class		E1
Dimensions and designs		
Roll		Roll 2 x 30 m
Number of designs available		2



The above information is subject to modification for the benefit of further improvement (06/09/2024). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.